


# i-Tie : 0627-SPU

Product  
Specification

(5.8mm x 270mm)



## Properties

### General

Product Code [model number]:	0627
Standard Pack Sizes:	Trade bags of 48. Retail bags of 24. Bulk box of 3000
Standard Colours:	Black, natural, green
Notes:	Other colours may be available subject to minimum order Supplied in tear-off sheets of 12 rapstraps

### Physical

Nominal Moulded Length:	270mm (11")
Width:	5.8mm (0.22")
Thickness:	3.25mm (0.13")
Weight:	3.1g approx.
Apertures:	48
Maximum Fitted Bundle Size:	> 75mm (3") diameter
Minimum Fitted Bundle Size:	< 10mm (0.4") diameter
Average uses per Strap:	3x (@20-40mm diameter)
Recommended maximum loading when looped:	12Kg
Recommended maximum stretch:	+20%

### Material

Material:	Polyurethane Elastomer [Soft durometer, 90A]
Density:	1230Kg/m <sup>3</sup> [approx.]
Maximum Tensile Strength:	50MPa (Elastic limit yield at 8MPa)
Flexural Modulus:	0.05GPa [approx.]
Resistance to Fuels and Oils:	Good to Excellent

### Thermal

Low Temperature Brittle Point:	-68°C (-90°F)
Minimum Installation Temp:	+10°C
Recommended Service Temp Range [no load]:	-20°C to +60°C (-4°F to +140°F)
Recommended Ambient Temp:	15°C to 28°C
Recommended Ambient Humidity:	40-60% RH
Short Temp Peak Temp Range [no load]:	-30°C to +80°C (-22°F to +176°F)

### Flame & UV

Flammability UL94 Flame Class:	1.5mm (0.06") Thickness, Class HB
UV Properties:	Some loss of physical properties & discolouration may occur after prolonged outdoor exposure

All data provided for representation only. E&OE.

**Rapstrap**<sup>®</sup>  
Thousands of uses. Only one rapstrap.

Rapstrap Ltd., Expo House, Mead Lane, Hertford, Hertfordshire SG13 7AP, UK  
e: [enquiries@rapstrap.com](mailto:enquiries@rapstrap.com) [www.rapstrap.com](http://www.rapstrap.com)

Registered Office: Rapstrap Limited, Five Ways, 57/59 Hatfield Road, Potters Bar, Herts, EN8 1HS, UK. Registered in England & Wales Company No. 05861045

21.61